



**Engine Model / Mount Cross Reference / 4 Point Mountings**

Engine Model	Weight lbs	Hp Range	Suggested Mount *	Hole Centers	Stud Size
Stern Drive & Inboard Installations					
All 4 and 6 Cylinder and V8 GAS Engines	500-1200	80-500+	<a href="#">DF-216</a>	4.0"	3/4" - 16
All 4 and 6 Cylinder and V8 GAS Engines	Up to 800	80-375	<a href="#">Use DF-206 for 5/8" stud</a>	4.0"	5/8" - 18
Gas Inboard Rear Mount (Transmission End)	500-1200	80-500+	<a href="#">RM-1060</a>	4.0"	3/4" - 16
<b>Caterpillar Diesel Engines</b>					
	Weight lbs	Hp Range	Suggested Mount *	Hole Centers	Stud Size
3116/3126/C7/C9	1500-2400	205-500	<a href="#">DF-9106</a>	5.0"	1" - 14
3208/3304B	1700-2200	85 up to 340	<a href="#">DF-238-M1</a>	5.0"	3/4" - 16
3208	1700-2600	>340	<a href="#">DF-4408-4</a>	5.0"	1" - 14
3308C/3406E/3176B/3306C	1600-3800	500-820	<a href="#">DF-4407-4 Light end</a>	5.0"	1" - 14
			<a href="#">DF-4428-4 Heavy end</a>	9.0"	1" - 14 @ 2
<b>Chris-Craft Engines</b>					
	Weight lbs	Hp Range	Suggested Mount *	Hole Centers	Stud Size
181-F	650	130	<a href="#">DF-2207-2</a>	4.0"	5/8" - 18
305-F/350K/350KBM	500-1200	250-330	<a href="#">DF-216</a>	4.0"	3/4" - 16
	Up to 800	250-330	<a href="#">Use DF-206 for 5/8" stud</a>	4.0"	5/8" - 18
All 454 engines	1200	330-425	<a href="#">DF-216</a>	4.0"	3/4" - 16
<b>Cummins Diesel Engines</b>					
	Weight lbs	Hp Range	Suggested Mount *	Hole Centers	Stud Size
4BT/6BT	900-1600	80-370	<a href="#">DF-477-M3</a>	5.0"	3/4" - 16
6C/420 Diamond	1800-2300	150-450	<a href="#">DF-9106</a>	5.0"	1" - 14
V-504/555-M	1800-2200	200-250	<a href="#">DF-238-M1</a>	5.0"	3/4" - 16
VT-555-M	2200-	270	<a href="#">DF-4407-4</a>	5.0"	1" - 14

	2500				
V-903-M	2800	305-360	<a href="#">DF-4408-4</a>	5.0"	1" - 14
NTA855, QSM 11 Engines	2800-4200	215-635	<a href="#">DF-4408-4 Light end</a>	5.0"	1" - 14
			<a href="#">DF-4428-4 Heavy end</a>	9.0"	1" - 14 @ 2
<b>Detroit Diesel Engines</b>	<b>Weight lbs</b>	<b>Hp Range</b>	<b>Suggested Mount *</b>	<b>Hole Centers</b>	<b>Stud Size</b>
6.2/4-53/8.2/6V53/6V53T/471N	700-2400	130-420	<a href="#">DF-238-M1</a>	5.0"	3/4" - 16
471TI/6-71/6-71TI/6V71/6V71TA	2200-2800	250-550	<a href="#">DF-4408-4</a>	5.0"	1" - 14
8V71/8V71TI					
6V92/6V92TA/8V92/8V92TA	3500-4200	650-720	<a href="#">DF-4408-4 Light end</a>	5.0"	1" - 14
			<a href="#">DF-4428-4 Heavy end</a>	9.0"	1" - 14 @ 2
<b>Duetz Engines</b>	<b>Weight lbs</b>	<b>Hp Range</b>	<b>Suggested Mount *</b>	<b>Hole Centers</b>	<b>Stud Size</b>
F1L208/F1L210/F1L511/F2L511	190-425	9-35	<a href="#">DF-2205-2</a>	4.0"	5/8" - 18
F2L912/F3L912/F4L/912/F5L912					
F6L912/BF6L913	600-1200	36-200	<a href="#">DF-216</a>	4.0"	3/4" - 16
	Up to 800	36-200	<a href="#">Use DF-206 for 5/8" stud</a>	4.0"	5/8" - 18
V-6 & V-8 Engines	1250-2800	210-500	<a href="#">DF-4408-4</a>	5.0"	1" - 14
V-6 & V-8 Engines	3400-4200	520-600	<a href="#">DF-4408-4 Light end</a>	5.0"	1" - 14
			<a href="#">DF-4428-4 Heavy end</a>	9.0"	1" - 14 @ 2
<b>Ford Engines</b>	<b>Weight lbs</b>	<b>Hp Range</b>	<b>Suggested Mount *</b>	<b>Hole Centers</b>	<b>Stud Size</b>
LSG/CSG/WSG (Gas engines)	200-480	120-245	<a href="#">DF-206</a>	4.0"	5/8" - 18
YSD-424/YSD-635/SSD437/ DSD-442 (Gas engines)	500-800	250-325	<a href="#">DF-216</a>	4.0"	3/4" - 16
SSD655N/655T/DSD659/ DSD659/660/662 (Gas engines)	950-1500	300-480	<a href="#">DF-236-M1</a>	5.0"	3/4" - 16
DSD-681N/T (Gas engines)	1500-	500	<a href="#">DF-237-M1</a>	5.0"	3/4" - 16

	1600				
Lehman & Merlin Diesel	2800	300-475	<a href="#">DF-4408-4</a>	5.0"	1" - 14
Ford Gas Generators VSG411/413/ LSG423	200-450	20-75	<a href="#">DF-2205-2</a>	4.0"	5/8" - 18
LSG875/CSG649	470-725	80-200	<a href="#">DF-2207-2</a>	4.0"	5/8" - 18
Ford Diesel Engines & Gen ESD442 Marine	290	80-100	<a href="#">DF-2205-2</a>	4.0"	5/8" - 18
All other ESD/BSD Series Engines	800-1400	150-300	<a href="#">DF-236-M1</a>	5.0"	3/4" - 16
<b>Isuzu Engines</b>	<b>Weight lbs</b>	<b>Hp Range</b>	<b>Suggested Mount *</b>	<b>Hole Centers</b>	<b>Stud Size</b>
QD27	400-500	14-28	<a href="#">DF-2207-2</a>	4.0"	5/8" - 18
QD40/60	500-750	40-60	<a href="#">DF-3304-3</a>	4.5"	3/4" - 16
QSD 130/145	1100-1400	130-145	<a href="#">DF-3306-3</a>	4.5"	3/4" - 16
<b>Iveco Engines</b>	<b>Weight lbs</b>	<b>Hp Range</b>	<b>Suggested Mount *</b>	<b>Hole Centers</b>	<b>Stud Size</b>
8041SRM15/8061M05	900-1500	140-150	<a href="#">DF-236-M1</a>	5.0"	3/4" - 16
8061SM05/06/8061SRM 05 & 06 & 27	1160-1800	190-270	<a href="#">DF-237-M1</a>	5.0"	3/4" - 16
8361SRM10 & 37	1500-1800	285-420	<a href="#">DF-4407-4</a>	5.0"	1" - 14
8281SRM70	3700-4200	500-700	<a href="#">DF-4408- 4 Light end</a>	5.0"	1" - 14
			<a href="#">DF-4428-4 Heavy end</a>	9.0"	1" - 14 @ 2
<b>John Deere Engines</b>	<b>Weight lbs</b>	<b>Hp Range</b>	<b>Suggested Mount *</b>	<b>Hole Centers</b>	<b>Stud Size</b>
3.9 Liter & 4.5 Liter	1000-1200	70-150	<a href="#">DF-236-M1</a>	5.0"	3/4" - 16
6.8 Liter	1500-1800	155-320	<a href="#">DF-237-M1</a>	5.0"	3/4" - 16
7.6 & 8.1 Liter	1800-2200	240-450	<a href="#">DF-238-M1</a>	5.0"	3/4" - 16
12.5Liter	2500-	240-450	<a href="#">DF-4408</a>	5.0"	1" - 14

	<b>2800</b>				
<b>Peninsular Diesel Engines</b>	<b>Weight lbs</b>	<b>Hp Range</b>	<b>Suggested Mount *</b>	<b>Hole Centers</b>	<b>Stud Size</b>
All Models	500-2000	110-450	<a href="#">DF-238-M1</a>	5.0"	3/4" - 16
<b>Perkins Engines</b>	<b>Weight lbs</b>	<b>Hp Range</b>	<b>Suggested Mount *</b>	<b>Hole Centers</b>	<b>Stud Size</b>
M20/M30	240-300	17-50	<a href="#">DF-2205-2</a>	4.0"	5/8" - 18
M35 - M90NA	450-650	33.5-80	<a href="#">DF-2207-2</a>	4.0"	5/8" - 18
4-108M/4-154M	465-700	50-60	<a href="#">DF-2207-2</a>	4.0"	5/8" - 18
M135/165T/200TI/240TI/275TI					
4-236M	840-1500	85-250	<a href="#">DF-236-M1</a>	5.0"	3/4" - 16
T6-3544M/ST6-3544M					
SSTT6-3544M	1250-2100	135-200	<a href="#">DF-4406-4</a>	5.0"	1" - 14
TV8-540M	2200-2500	350	<a href="#">DF-4407-4</a>	5.0"	1" - 14
<b>Renault Engines</b>	<b>Weight lbs</b>	<b>Hp Range</b>	<b>Suggested Mount *</b>	<b>Hole Centers</b>	<b>Stud Size</b>
RC8D/11D/12D/16D	180-450	0-20	<a href="#">DF-2205-2</a>	4.0"	5/8" - 18
RC30D	500-700	30-50	<a href="#">DF-2207-2</a>	4.0"	5/8" - 18
RC55D/80D/90D/RC130DTS& 140	750-1400	55-160	<a href="#">DF-236-M1</a>	5.0"	3/4" - 16
<b>Universal Engines</b>	<b>Weight lbs</b>	<b>Hp Range</b>	<b>Suggested Mount *</b>	<b>Hole Centers</b>	<b>Stud Size</b>
Model 12, 18, 20, 25, 25XP, 30	175-450	0-35	<a href="#">DF-2205-2</a>	4.0"	5/8" - 18
Model 40, 50	490 - 700	40-50	<a href="#">DF -2207-2</a>	4.0"	5/8" - 18
M3-20/M4-30	235-450	18-25	<a href="#">DF-2205-2</a>	4.0"	5/8" - 18
5444/M4-44&50	480-550	45-60	<a href="#">DF-206</a>	4.0"	5/8" - 18
ATOMIC 1	130	10	<a href="#">DF-2204-2</a>	4.0"	5/8" - 18
ATOMIC 2/ ATOMIC 4 / STEVEDORE (Includes model 5411, 5416, 5424)	175-335	0-30	<a href="#">DF-2205-2</a>	4.0"	5/8" - 18
ATOMIC Model 5432	490	30-40	<a href="#">DF-2207-2</a>	4.0"	5/8" - 18

<b>Volvo Diesel Engines</b>	<b>Weight lbs</b>	<b>Hp Range</b>	<b>Suggested Mount *</b>	<b>Hole Centers</b>	<b>Stud Size</b>
MD5A/6B/7A	245-385	7.5-13	<a href="#">DF-2205-2</a>	4.0"	5/8" - 18
MD11C/17C/MD17C-110S/MD21A	500-750	23-61	<a href="#">DF-2207-2</a>	4.0"	5/8" - 18
TMD31/TAMD31/MD32A	740-900	62-150	<a href="#">DF-3304-3</a>	4.5"	3/4" - 16
TMD40A/TMD40A/TMD41/TAMD41	1000-1100	117-200	<a href="#">DF-3306-3</a>	4.5"	3/4" - 16
TAMD60A/61/MD70B/TAMD70B/C	1800-2200	150-310	<a href="#">DF-238-M1</a>	5.0"	3/4" - 16
TAMD42/THAMD70C/TAMD71/MD70E	2000-2400	200-430	<a href="#">DF-4407-4</a>	5.0"	1" - 14
TMD120A/TAMD120A/TAMD122	2200-4200	260-450	<a href="#">DF-4408-4 Light end</a>	5.0"	1" - 14
			<a href="#">DF-4428-4 Heavy end</a>	9.0"	1" - 14 @ 2
<b>Westerbeke</b>	<b>Weight lbs</b>	<b>Hp Range</b>	<b>Suggested Mount *</b>	<b>Hole Centers</b>	<b>Stud Size</b>
W-10, W13, W18, W21, W21A, W27	200-450	0-27	<a href="#">DF-2205-2</a>	4.0"	5/8" - 18
W33, W46, W52, W58, W70	500 - 750	33-70	<a href="#">DF-2207-2</a>	4.0"	5/8" - 18
W80, W100, W120	800 - 1400	80-120	<a href="#">DF-236-M1</a>	5.0"	3/4" - 16
<b>Yanmar Engines</b>	<b>Weight lbs</b>	<b>Hp Range</b>	<b>Suggested Mount *</b>	<b>Hole Centers</b>	<b>Stud Size</b>
GM Series	100-320	9-28	<a href="#">DF-2205-2</a>	4.0"	5/8" - 18
3JH Series	390-425	35-50	<a href="#">DF-2205-2</a>	4.0"	5/8" - 18
4JH Series	490-550	50-100	<a href="#">DF-2207-2</a>	4.0"	5/8" - 18
4LH Series	750-900	110-170	<a href="#">DF-3304-3</a>	4.5"	3/4" - 16
6LP Series	700-900	260-315	<a href="#">RM-1060</a>	4.0"	3/4" - 16
6LYA-CX Series	1300-1500	315-465	<a href="#">DF-9106</a>	5.0"	1" - 14
6CX- GTE2 Series	1800-2400	490-500	<a href="#">DF-9106</a>	5.0"	1" - 14

---

**Note 1: DF2200 Series Mounts available as DF2200 - 2 (with 5/8" stud) or DF-2200-1 (with 1/2" stud)**

**Note 2: Use DF-3300 Series Mounts for 4 1/2" hole centers (with 3/4" stud)**

**Note 3: Use DF-100 Mount for 1 7/8" minimum clearance**

\*Suggested Mounts are based on actual applications - make sure to compare the listed mount weight capacities against your actual combined engine, gear, and other engine mounted accessory weights.

Do not exceed listed four (4) point mounting capacities.

---